

IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) A digital television receiver **system** comprising:
a[[n]] **first** equalizer having an input for receiving a transmitted digital data stream comprising a plurality of field syncs, a plurality of segments of symbol spaces between successive ones of the field syncs, and a plurality of echo cancellation reference signals are positioned between the field syncs, wherein the plurality of echo cancellation reference signals are positioned at respective locations between the field syncs according to a desired temporal rate coverage of dynamically changing echoes, the **first** equalizer operatively processing the digital data stream at the input thereof with the echo cancellation reference signals to provide a substantially echo-free digital data stream at an output thereof; and
a digital television receiver having **a second equalizer and** an input coupled to the output of the **first** equalizer.
2. (Currently Amended) The digital television receiver system as in claim 1, wherein the digital data stream at the output of the **first** equalizer includes the echo cancellation reference signals, further comprising a temporary memory coupled to the output of the equalizer for removal of the echo cancellation reference signals from the digital data stream, the digital television receiver being coupled to the output of the **first** equalizer through the temporary memory.

3. (Original) The digital television receiver system as in claim 2, wherein the transmitted digital data stream is an ATSC VSB digital data stream into which the echo cancellation reference signals are inserted prior to transmission thereof, and the digital television receiver is a standard VSB television receiver.

4. (Original) The digital television receiver system as in claim 1, wherein:
at least some of the symbol spaces in the transmitted digital data stream are blank and are functionally related to the echo cancellation reference signals to form macro echo cancellation reference assembly signals; and

the digital data stream at the output of the equalizer includes the macro echo cancellation reference assembly signals;

the digital television receiver system further comprising a temporary memory coupled to the output of the equalizer for removal of the macro echo cancellation reference assembly signals from the digital data stream, the digital television receiver being coupled to the output of the equalizer through the temporary memory.

5. (Original) The digital television receiver system as in claim 2, wherein the transmitted digital data stream is an ATSC VSB digital data stream into which the macro echo cancellation assembly signals are inserted prior to transmission thereof, and the digital television receiver is a standard VSB television.

6. (Original) The digital television receiver system as in claim 1, wherein:
the transmitted digital data stream is an ATSC VSB digital data stream into which
the echo cancellation reference signals are inserted prior to transmission thereof;
the digital data stream at the input of the receiver includes the echo cancellation
reference signals; and
the digital television receiver is a VSB television receiver.

7. (Previously Presented) A digital television receiver comprising:
an equalizer having an input for receiving a transmitted digital data stream
comprising a plurality of field syncs, a plurality of segments of symbol spaces between
successive ones of the field syncs, and a plurality of echo cancellation reference signals
between the field syncs, the equalizer operatively processing the digital data stream at the
input thereof with the echo cancellation reference signals to provide a substantially echo-
free digital data stream at an output thereof; and

a digital television receiver having an input coupled to the output of the equalizer,
wherein

the transmitted digital data stream is an ATSC VSB digital data stream into which
the echo cancellation reference signals are inserted prior to transmission thereof;

the digital data stream at the input of the receiver includes the echo cancellation
reference signals; and

the digital television receiver is a VSB television receiver, wherein

the VSB television receiver is a modified standard VSB television receiver
comprising:

means for identifying and skipping the echo cancellation reference signals in the digital data stream at the input of the modified standard VSB television receiver;

means for handling any break up during transmission of convolution codes in the transmitted data stream so that sequential switching sites in the modified standard VSB television receiver operate properly;

means for picking up unlinked data in the transmitted digital data stream and linking the unlinked data to prior states thereof; and

a modified data interleaver for maintaining order when the convolution codes are discontinuous.

8. (Original) The digital television receiver system as in claim 1, wherein:

at least some of the symbol spaces in the transmitted digital data stream are blank and are functionally related to the echo cancellation reference signals to form macro echo cancellation reference assembly signals;

the digital data stream at the input of the receiver includes the macro echo cancellation reference assembly signals;

the transmitted digital data stream is an ATSC VSB digital data stream into which the macro echo cancellation reference assembly signals are inserted prior to transmission thereof; and

the receiver is a VSB television receiver.

9. (Previously Presented) A digital television receiver comprising:

an equalizer having an input for receiving a transmitted digital data stream comprising a plurality of field syncs, a plurality of segments of symbol spaces between successive ones of the field syncs, and a plurality of echo cancellation reference signals between the field syncs, the equalizer operatively processing the digital data stream at the input thereof with the echo cancellation reference signals to provide a substantially echo-free digital data stream at an output thereof; and

a digital television receiver having an input coupled to the output of the equalizer, at least some of the symbol spaces in the transmitted digital data stream are blank and are functionally related to the echo cancellation reference signals to form macro echo cancellation reference assembly signals;

the digital data stream at the input of the receiver includes the macro echo cancellation reference assembly signals;

the transmitted digital data stream is an ATSC VSB digital data stream into which the macro echo cancellation reference assembly signals are inserted prior to transmission thereof; and

the receiver is a VSB television receiver,

wherein the VSB television receiver is a modified standard VSB television receiver comprising:

means for identifying and skipping the macro echo cancellation reference assembly signals in the digital data stream at the input of the modified standard VSB television receiver;

means for handling any break up during transmission of convolution codes in the transmitted digital data stream so that sequential switching sites in the modified standard VSB television receiver operate properly;

means for picking up unlinked data in the transmitted digital data stream and linking the unlinked data to prior states thereof; and

a modified data interleaver for maintaining order when the convolution codes are discontinuous.

10. (Currently Amended) A digital television receiver system as in claim 1, wherein the first equalizer comprises:

an extraction circuit for extracting copies of the echo cancellation reference signals from the digital data stream at the input of the equalizer;

a microprocessor coupled to the extraction circuit for calculating filter coefficients from the extracted copies of the echo cancellation reference signals; and

a filter receiving the digital data stream from the input of the equalizer coupled to the microprocessor for substantially canceling echo interference from the transmitted digital data stream.

11. (Original) The digital television receiver system as in claim 10, wherein the filter comprises a FIR filter section and an IIR filter section.

12. (Original) The digital television receiver system as in claim 1, wherein:
the transmitted digital data stream is transmitted over a transmission path; and
the echo cancellation reference signal is non-cyclic, has a substantially flat
frequency response within the bandwidth of said transmission path, has a large plurality
of amplitude peaks over a time interval, and has proportionally shorter tails relative to the
large plurality of amplitude peaks.

13. (Previously Presented) The digital television receiver system as in claim 1,
wherein the echo cancellation reference signal is of a class of signals substantially
defined by

$$f(t) = \frac{1}{2\pi} \int_0^{\Omega} [A \cos (b\omega^2) + jA \sin (b\omega^2)] e^{j\omega t} d\omega \\ + \frac{1}{2\pi} \int_{-\Omega}^0 [A \cos (-b\omega^2) + jA \sin (-b\omega^2)] e^{j\omega t} d\omega$$

wherein A, b and Ω are real numbers.

14. (Previously Presented) The digital television receiver system as in claim 1,
wherein successive ones of the field syncs contain therebetween only one echo
cancellation reference signal.

15. (Previously Presented) The digital television receiver system as in claim 1,
wherein successive ones of the field syncs contain therebetween a plurality of echo
cancellation reference signals.

16. (Previously Presented) A method of processing a digital data stream having echo interference from transmission over a transmission path, the digital data stream having a plurality of field syncs and a plurality of segments of symbol spaces between successive ones of the field syncs, the method comprising:

identifying a plurality of echo cancellation reference signals between the field syncs;

processing the digital data stream with the echo cancellation reference signals to provide a substantially echo-free digital data stream; and

furnishing the substantially echo-free digital data stream to a digital television receiver;

wherein the echo cancellation reference signals are of a class of signals substantially defined by

$$f(t) = \frac{1}{2\pi} \int_0^{\Omega} [A \cos (b\omega^2) + jA \sin (b\omega^2)] e^{j\omega t} d\omega \\ + \frac{1}{2\pi} \int_{-\Omega}^0 [A \cos (-b\omega^2) + jA \sin (-b\omega^2)] e^{j\omega t} d\omega$$

wherein A, b and Ω are real numbers.

17. (Original) The method as in claim 16, further comprising removing the echo cancellation reference signals from the substantially echo-free digital data stream subsequent to the processing step and prior to the furnishing step.

18. (Original) The method as in claim 16, wherein the identifying step further comprises identifying the echo cancellation reference assembly signals within a plurality of macro echo cancellation reference assembly signals.

19. (Original) A system for cancellation of echo interference in a transmitted data stream, comprising:

means for inserting a plurality of echo cancellation signals into an ATSC VSB digital data stream prior to transmission to generate a transmission digital data stream, the ATSC VSB data stream comprising a plurality of field syncs and a plurality of segments of symbol spaces between successive ones of the field syncs, and the echo cancellation reference signals being inserted between the field syncs and being of a class of signals substantially defined by

$$f(t) = \frac{1}{2\pi} \int_0^{\Omega} [A \cos(b\omega^2) + jA \sin(b\omega^2)] e^{j\omega t} d\omega \\ + \frac{1}{2\pi} \int_{-\Omega}^0 [A \cos(-b\omega^2) + jA \sin(-b\omega^2)] e^{j\omega t} d\omega$$

wherein A, b and Ω are real numbers;

means for transmitting the transmission digital data stream;

an equalizer having an input for receiving the transmission digital data stream, the equalizer operatively processing the transmission digital data stream at the input thereof with the echo cancellation reference signals to provide a substantially echo-free digital data stream at an output thereof; and

a VSB digital television receiver having an input coupled to the output of the equalizer.

20. (Previously Presented) A method for cancellation of echo interference in a transmitted data stream, comprising:

inserting a plurality of echo cancellation signals into an ATSC VSB digital data stream prior to transmission to generate a transmission digital data stream, the ATSC VSB data stream comprising a plurality of field syncs and a plurality of segments of symbol spaces between successive ones of the field syncs, and the echo cancellation reference signals being inserted between the field syncs and being of a class of signals substantially defined by

$$f(t) = \frac{1}{2\pi} \int_0^{\Omega} [A \cos (b\omega^2) + jA \sin (b\omega^2)] e^{j\omega t} d\omega \\ + \frac{1}{2\pi} \int_{-\Omega}^0 [A \cos (-b\omega^2) + jA \sin (-b\omega^2)] e^{j\omega t} d\omega$$

wherein A, b and Ω are real numbers;

transmitting the transmission digital data stream;

subsequent to the transmitting step, processing the transmission digital data stream with the echo cancellation reference signals therein to provide a substantially echo-free digital data stream; and

applying the substantially echo-free digital data stream to a VSB digital television receiver.

21. (Previously Presented) An ATSC 8 VSB digital television receiver system comprising:

an equalizer having an input for receiving a transmitted digital data stream comprising a plurality of field syncs, a plurality of segments of symbol spaces between successive ones of the field syncs, and a plurality of macro echo cancellation reference assembly signals between successive ones of the field syncs, each of the macro echo cancellation reference assembly comprising a plurality of blank symbol spaces and at least one echo cancellation reference signal, the equalizer operatively processing the digital data stream at the input thereof with the echo cancellation reference signals to provide a substantially echo-free digital data stream at an output thereof;

a FIFO register to operatively remove the echo cancellation reference signals from the digital data stream at the output of the equalizer; and

a standard 8 VSB digital television receiver having an input coupled to the output of the FIFO register;

wherein the echo cancellation reference signals are of a class of signals substantially defined by

$$f(t) = \frac{1}{2\pi} \int_0^{\Omega} [A \cos (b\omega^2) + jA \sin (b\omega^2)] e^{j\omega t} d\omega \\ + \frac{1}{2\pi} \int_{-\Omega}^0 [A \cos (-b\omega^2) + jA \sin (-b\omega^2)] e^{j\omega t} d\omega$$

A, b and Ω being real numbers.

22. (New) The digital television receiver system as in claim 1, wherein the digital television receiver is a standard VSB television receiver.